Piccolo and Euro fuel-oil burners

PICCOLO and EURO

FUEL-OIL BURNERS 16-265 kW

Flexible turndown range **High combustion efficiency Reliable construction** Easy and simple to maintenance **Silent operation**











General information:

Having developed the Piccolo and Euro type burner series, we should like to offer economic, efficient and modern firing devices for the users. To fulfill the continuously rising requirements, burners have low dimensions, shatter-proof plastic cover, and excellent noiseinsulation. The manufactured components of the burners are made from reliable materials. Designing, easy maintenance, assemblage, and adjusting were taken into consideration. The burner house is fixed by one piece screw only. Operation is silent, due to the conscentious design of the combustion-air inlet. The air damper is closed at stand-by position. Piccolo type burners are ON/OFF, Euro type burners could be ON/OFF or HIGH/LOW controlled, respectively. The simple construction makes quick fitting and set-up possible, the use of the excellent-quality safety-, and control devices results in low maintenance cost. Combustion is perfect, due to the fine-adjusting of the air retention head. Air volume is adjustable by a parabolic-profile excenter. By the moveable burner-boiler flange, the burner can be taken out, without dismounting the flange from the boiler. Such a solution makes the burner-fitting on the boiler very easy. Commissioning relevant legislations and standards have to be observed.


These burners can be mounted on the following domestic and communal heating appliances:


- boilers
- hot-air blowers


Advantages:

- high combustion efficiency
- flexible turndown range
- stable flame
- simple and fast electric connection with multi-poled connectors
- simple assemblage, quick maintenance
- silent operation
- environment-safe, low-pollutant emission
- reliable construction
- long-life operation

Fuel-oil supply system schemes:







* at Euro-15 és 25 types under developing

Attachments:

- 1 Fuel-oil pump
- 3 Solenoid valve
- 5 Flexible hosing
- 6 Tee-piece
- 7 Oil-filter
- 8 Fitting

Optionals for special request:

9 Manual globe-cock




HUNGARY

Main technical data:

Туре	PICCOLO-O	Euro-6-O	Euro-9-O	Euro-10-O	Euro-15-O	Euro-25-O	
Output range	16-36 kW	33-75 kW	70-115 kW	70-120 kW	95-160 kW	130-265 kW	
Fuel	Light fuel-oil						
Mode of output control	ON/OFF				ON/OFF or HIGH/LOW *		
Turndown ratio	-				1:2		
Primary burner control	Satronic TF 974						
Flame detector	Satronic MZ 770						
Ignition	Automatically, by high voltage spark						
Electrical connection	230 V, 50 Hz+PE						
El. power consumption	196 W	196 W	196 W	206 W	230 W	240 W	
Electrical protection	IP 20						
Noise level	62 db (A)						
Weight	12 kg				25 kg		

^{*} at Euro-15 and -25 types HIGH/LOW versions under developing.


Outline drawing and connecting dimensions:




Til (Dimensions:						
Flange mounting holes on the boiler	Type	Piccolo-O	Euro-6-O	Euro-9-O	Euro-10-O	Euro-15-O	Euro-15-O
	Α	258-353	300-375	300-382	300-382	310-450	340-370
	В	250	301	301	301	385	385
	C	216	281	281	281	370	370
	D	163	225	225	225	295	295
	G	45-140	45-120	88-170	88-170	90-230	150-180
	I	210	245	245	245	270	270
	φK	80	80	95	100	114	144
	φLW	90	100	115	120	125	155
φ M	φM	150	150	150	150	180	200
· ·	N	M 8	M 8	M 8	M 8	M 10	M 10



Furnace chamber pressure – burner output characteristics:



Fuel-oil burner type symbols:



Regional Sales Office:

Transdanubian Sales Office:	H-8300 Tapolca Juhász Gy. u. 2/	1., Hungary	Tel/F.:+36-87-510-670
Your regional dealer:			

